

EPPCO ADVANCED V50

PRODUCT DESCRIPTION

EPPCO ADVANCED V50 is a high performance diesel engine oil for use in high output and turbocharged engines. It is available in SAE 20W-60 viscosity grade and has been developed using CH-4 chemistry for mixed fleet operations where European, US and Japanese heavy and light duty trucks are used.

APPLICATIONS

- ◆ Modern turbocharged and intercooled heavy goods vehicles
- ◆ Heavy earth moving equipment used in the construction industry
- ◆ Long distance coach operations
- ◆ Mixed fleet vehicle operations
- ◆ High speed diesels used in offshore marine applications
- ◆ Stationary power generation units using high speed diesel engines

PERFORMANCE STANDARDS

ADVANCED V50 meet the testing requirements of following International Specifications in appropriate viscosity:

API CH-4

Always follow the equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ADVANCED V50 provides:

- ◆ **Excllent Engine Cleanliness**
- ◆ **Helps Maintain Engine Efficiency**
- ◆ **Proven TBN Retention Reserve**

Technical Data*	
SAE Grade	25W-60
Density at 15°C, kg/L, ASTM D4052	0.884
Kinematic Viscosity mm ² /s @ 40°C, ASTM D 445	249
Kinematic Viscosity mm ² /s @ 100°C, ASTM D 445	25
Viscosity Index, ASTM D 2270	132
Flash Point, COC, °C, ASTM D 92	256
Pour Point, °C, ASTM D 97	-21
TBN, mg KOH/g, ASTM D 2896	11.0
CCS Viscosity, mPa.s, ASTM D 5293	7569 @-10°C
Density at 15°C, kg/L, ASTM D4052	300094

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.