



EPPCO ADVANCED 880X 15W-40

PRODUCT DESCRIPTION

EPPCO ADVANCED 880X 15W-40 is advanced heavy duty diesel engine oil for low emission engines operating on high temperature using low sulphur fuel and fitted with exhaust after treatment devices such as Three Way Catalyst (TWC), Diesel particulate filters (DPF), Selective Catalyst Reduction (SCR), Diesel Particulates & Nitrous-oxide Reduction(DPNR), Exhaust Gas Recirculation(EGR). It is available in SAE 15W-40 viscosity grade. Formulated to provide excellent engine piston deposit control.

APPLICATIONS

- ◆ Heavy duty Diesel Vehicles fitted with state-of-the art exhaust after treatment system such as particulate filters, EGR and catalytic converters that meets low emission requirements EURO IV & V
- ◆ Off-road construction equipments
- ◆ Light duty diesel passenger cars & pickups.
- ◆ Suitable for both turbocharged and naturally aspirated diesel engines

PERFORMANCE STANDARDS

ADVANCED 880X 15W-40 is formulated with additive technology that has been tested to meet the requirements of following OEM and International specifications requirements:

API CJ4/SN, ACEA E9,

Also suitable for equipments calling for MB-Approval 228.31, MTU Type 2.1, Caterpillar ECF-3, Volvo VDS 4, MAN M3575 specifications.

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

ADVANCED 880X 15W-40 provides:

- ◆ Protection to Exhaust After Treatment Devices such as Three Way Catalyst (TWC), Diesel particulate filters (DPF), Selective Catalyst Reduction (SCR), Diesel Particulates & Nitrous-oxide Reduction(DPNR), Exhaust Gas Recirculation(EGR) thus suitable for low emission engines
- ◆ Superior resistance to oil thickening/sludge formation, outstanding deposit control and improve engine life
- ◆ Helps support standard oil drain interval and oil consumption control
- ◆ Excellent protection against wear
- ◆ Excellent low temperature easy starting, so termed as all weather oil

Technical Data*	
SAE Grade	15W-40
Density kg/m ³	0.8560
Kinematic Viscosity mm ² /s @ 40°C	106.2
Kinematic Viscosity mm ² /s @ 100°C	14.74
Viscosity Index	143
TBN mg KOH/g	8.0
Flash Point COC	234
Pour Point °C	-36
Product code	300040

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.